


AMERICAN STANDARD CHANNELS



Channel Size	Weight (lb/ft)	Area (in ²)	Depth (in)	Flange Width (in)	Flange Thickness (in)	Web Thickness (in)	Radius (in)	Centroidal X (in)	Centroidal Y (in)
C 15 x 50	15	3.716	0.716	14.7	50	404	11.0	53.8	3.78
C 15 x 40	15	3.520	0.520	11.8	40	349	9.23	46.5	3.37
C 15 x 33.9	15	3.400	0.400	9.96	33.9	315	8.13	42.0	3.11
C 10 x 30	10	3.033	0.673	8.82	30	103	3.94	20.7	1.65
C 10 x 25	10	2.886	0.526	7.35	25	91.2	3.36	18.2	1.48
C 10 x 20	10	2.739	0.379	5.88	20	78.9	2.81	15.8	1.32
C 10 x 15.3	10	2.600	0.240	4.49	15.3	67.4	2.28	13.5	1.16
C 8 x 18.75	8	2.527	0.487	5.51	18.75	44.0	1.98	11.0	1.01
C 8 x 13.75	8	2.343	0.303	4.04	13.75	36.1	1.53	9.03	0.85
C 8 x 11.5	8	2.260	0.220	3.38	11.5	32.6	1.32	8.14	0.78
C 6 x 13	6	2.157	0.437	3.83	13	17.4	1.05	5.80	0.64
C 6 x 10.5	6	2.034	0.314	3.09	10.5	15.2	0.87	5.06	0.56
C 6 x 8.2	6	1.920	0.200	2.40	8.2	13.1	0.69	4.38	0.49
C 4 x 7.25	4	1.721	0.321	2.13	7.25	4.59	0.43	2.29	0.34
C 4 x 5.4	4	1.584	0.184	1.59	5.4	3.85	0.32	1.93	0.28